


REV.	DESCRIPTION	DATE
A	New Drawing	2017/08/18

LTR	Part Name	Material	Description	QTY
1	Housing	Nylon UL94V-0	260°C for 10 Seconds . Initial : 1000M Ohms Min. After Test : 500M Ohms Min.	2
2	Contact	Brass	Current Rating : 2.0A Initial : 20m Ohms Max. After Test : 40m Ohms Max.	XX

Temperature Rating : -40°C ~ +125°C .
Dielectric Withstanding Voltage : 500V AC/Min



P.C.B LAYOUT

RoHS compliant

PHDS - RNXXXG1ABONX - BXXX

Series No

Plastic Base
N Vertical Duble Base

Number of Contact
01 to 40 contacts

Contact Plating
G1 Gold Flash

Base Color
B Black

Plastic
N NY-6T

Packing
G Box
A PE bag

PCB Contact Type
R Right Angle

Base
Type H x W (mm)
A 2.0 x 2.0

O Without locating Peg

竣豪電子股份有限公司
Superior Tech Co., Ltd.

General Tolerance	TITLE	Pitch 2.0mm Pin Header ,Right Angle	
X. ± 0.5	DRAWN	DATE	NO.
.X ± 0.3	Andy	08-18-17'	002
.XX ± 0.2	CHECK	DATE	PART NO.
.XXX ± 0.1	APPROVED	DATE	PHDS-RNXXXG1ABONX-BXXX
角度 ± 5°			CUSTOMER NO.

REV.	UNIT	SCALE	
A	mm	1:1	