


P.C.B LAYOUT

REV.	DESCRIPTION	DATE
A	New Drawing	2023/03/24

LTR	Part Name	Material	Description	QTY
1	Housing	Nylon UL94V-0	260°C for 10 Seconds . Initial : 1000M Ohms Min. After Test : 500M Ohms Min.	2
2	Contact	Brass	Current Rating : 2.0A Initial : 20m Ohms Max. After Test : 40m Ohms Max.	XX

Temperature Rating : -40°C ~ +125°C .  
Dielectric Withstanding Voltage : 500V AC/Min

PHDD-DDXXXG1ABONG-AXXX



RoHS compliant

竣豪電子股份有限公司  
**Superior Tech Co., Ltd.**

General Tolerance	TITLE	2.0x2.0mm Pin Header ,Straight Dual Row,Double Plastic Base	
X. ± 0.5	DRAWN	DATE	NO.
.X ± 0.3	Tom	03-24-23'	002
.XX ± 0.2	CHECK	DATE	PART NO.
.XXX ± 0.1	APPROVED	DATE	PHDD-DDXXXG1ABONG-AXXX
角度 ± 5°			CUSTOMER NO.

REV.	UNIT	SCALE	
A	mm	1:1	

(Q2-R03-01A) ST-R05-07