



 : SOLDER AREA

TOLERANCE: ± 0.05 ,
RECOMMENDED PCB LAYOUT
(TOP VIEW)

Number of Contact
80 Contact

Contact Plating	
G1	Gold flash

H	2.50mm
---	--------

Base Color	
N	Natural

Plastic	
L	LCP

Packing

Reel
Reel+Mylar

W	With locating Peg with fitting nail
----------	-------------------------------------

RoHS compliant

REV.	DESCRIPTION	DATE
A	最新版	2012/01/16
B	更新图面版本	2017/05/11

LTR	Part Name	Material	Description	QTY
1	Housing	LCP UL94V-0	+30%GF Initial : 1000M Ohms Min.	1
2	Contact	Brass C2680	Current Rating : 0.5 A Initial : 30m Ohms Max.	80
3	Fitting Nail	Brass C2680	Current Rating : 0.5 A Initial : 30m Ohms Max.	2
4	MYLAR	PI	_____	1

Temperature Rating : -40°C ~ +105°C .

Dielectric Withstanding Voltage : 300 V AC/Min

Circuit No.	Dimensions					
	A	B (A+5.5)	C (A+2.6)	D (A+3.5)	E (A-0.5)	F (A+2.5)
2*40P	19.50	25.00	22.10	23.00	19.00	22.00

竣豪電子股份有限公司
Superior Tech Co., Ltd.

竣豪電子股份有限公司 <i>Superior Tech Co., Ltd.</i>				General Tolerance		TITLE PH0.5 BTOB H2.5 母座成品图					
				X. ± 0.5		DRAWN Tom		DATE 2017/05/11		DWG.NO. 002	
				.X ± 0.3							
				.XX ± 0.2		CHECK		DATE		PART NO. BAAC-080G1250NWLX-B	
				.XXX ± 0.1							
REV. B	UNIT mm	SCALE 1:1		角度	± 5°	APPROVED		DATE		CUSTOMER NO.	