

REV.	DESCRIPTION	DATE
A0	New Drawing	2007/3/10

Specifications

Current Rating: 3A AC, DC

Voltage Rating: 250 AC Maximum

Operating Temp: -25°C`+85°C

Contact Resistance: 20M Ω Mix

Insulation Resistance: 1000M Ω Min

Terminal Material: Brass/Tin-plated/Gold-plated

Material:Nylon 66,UL94V-2

*未注公差按以下所示:

Tolerance	Unless	Otherwise Specified
.X	±0.35	
.XX	±0.25	

備注:A,B尺寸公差如下:
*2Pin~12Pin±0.35mm
13Pin~20Pin±0.5mm

poles	Dimension mm(in.)	
	A	B
2	2.54(0.100)	5.64(0.222)
3	5.08(0.200)	8.16(0.321)
4	7.62(0.300)	10.72(0.422)
5	10.16(0.400)	13.30(0.524)
6	12.70(0.500)	15.78(0.621)
7	15.24(0.600)	18.40(0.724)
8	17.18(0.700)	20.80(0.819)
9	20.32(0.800)	23.50(0.925)
10	22.86(0.900)	26.00(1.024)
11	25.40(1.000)	28.50(1.122)
12	27.94(1.100)	31.00(1.220)
13	30.48(1.200)	33.50(1.319)
14	32.02(1.300)	36.00(1.147)
15	35.56(1.400)	38.50(1.516)
16	38.10(1.500)	41.20(1.622)
17	40.64(1.600)	43.60(1.717)
18	43.18(1.700)	46.32(1.824)
19	45.72(1.800)	48.80(1.921)
20	48.26(1.900)	51.34(2.021)

竣豪電子股份有限公司
Superior Tech Co., Ltd.

General Tolerance

TITLE

2.54mm Wire-to-Board HOUSING

X. ± 0.5

DRAWN

DATE

NO.

.X ± 0.3

Yuanpengfei

03-10-07'

.XX ± 0.2

CHECK

DATE

PART NO.

.XXX ± 0.1

Hanping


03-10-07'

WRFB-H-XX

REV.

UNIT

SCALE



角度

± 5°

APPROVED

YEH

DATE

03-10-07'

CUSTOMER NO.

A0

mm

4:1